

INSTALLATION GUIDE

For hydraulic information panel type: SM8980-12V/SM8980-24V

SIDE-POWER
Thruster Systems



Important!

This panel will only work with Side-Power hydraulic systems and 5 lead control cable system. The panel is waterproof from the front end when correctly installed. However, you must ensure that they can never be submerged in water as this might cause a short-circuit.

Parts list referring to drawing below

Ref:	Pcs.	Parts
1	1 x	Information panel
2	1 x	Gasket
3	4 x	Screws (A4)
4	1 x	Corner clips

We Sleipner Motor AS declare that this information panel complies with health and safety requirements according to the Directive 89/336/EEC of 23 May 1989 amended by 92/31/EEC and 93/68/EEC.



Installation:

Find a comfortable position for the panel where it does not obstruct or is obstructed by other controls. Use the enclosed cut-out pattern to mark the area. Cut out the circular area as shown on pattern. If the front surface around your cut out is jagged or chipped, use a sealant to assist the gasket.

- A.** Check that the gasket (2), in its designated track in the back face of the panel (1), is mounted.
- B.** Connect the contact with the control cable from the control box.
- C.** Connect the contact with the control cable from the control box.
- D.** Put the panel (1) in place and screw in and tighten the four screws (3).
- E.** Press gently each of the four corner clips (4) into their corner slot.