

8000

General features



Standard module

Most functions are sized with 22 mm width.

Devices complete of mounting frame and cover plates

Some functions are realized in a monobloc version: device + mounting frame + cover plate. Equipments for rectangular mounting boxes are also provided with 1 extra gang for the mounting of devices with standard module.

Special module

Some of the most important functions (i.e. socket outlets, push buttons, name-plate push buttons, etc.) are realized with a module 25x45 mm, sized from 1 to 4 special modules. The adaptor allows the mounting of device sized 1 standard module beside special module device on mounting frame with 3, 4, 5 special modules.



Terminals.

Placed on the back of the device, with captive screws with cross-slotted head. Protected terminals with double entry for 1 or 2 rigid or flexible cables, sized from 0,75 mm² to 4 mm².



Mounting frame.

3-standard-module with captive screws.



Cover plate.

Complete and valorize the function; available in:

Metal: anodized aluminium bronze and black;

Resin: white and ivory

Resin Color: white, ivory and ivory-gold.



Single packing in box with barcode

The appliance is protected against knocks, dropping and dust and is well identified. In all cases where the methods of installation are not obvious, the appliances are equipped with an instruction sheet. The EAN 13 barcode, used by over 100 countries, is printed on every level packing and permits automatic inventory management with optical readers and computer systems connected to them.